

SPECIFICATIONS

MVC3000-H

COLOR BULLET CAMERA MVC3000-H (1/3" SONY CCD)

IMAGE SENSOR	INTERLINE TRANSFER CCD1/3" FORMAT
EFFECTIVE PIXEL	786(H)X494(V) (HIGH RESOLUTION)
SCANNING SYSTEM	2:1 INTERLACED
SYNC SYSTEM	INTERNAL SYNC
SYNC PLUSE	15.734KHz+1%(H)/15.625KHz+1%(H) 59.94Hz+1%(V)/50Hz+1%(V) SUB-CARRIER 3.57MHz+30ppm
RESOLUTION	470 LINES(H)
S/N RATIO	MORE THAN 46dB(typ)
GAMMA CHARACTERISTICS	0.45
MINIMUM ILLUMINATION	0.3 LUX(FI.2 10 IRE)
VIDEO OUTPUT	COMPOSITE VIDEO SIGNAL:1.0 Vp-p
WHITE BALANCE	AUTO WHITE BALANCE
ELECTRONIC SHUTTER	1/60-1/100,000 SEC.(N) 1/50-1/100,000 SEC.(P)
POWER SUPPLY	DC 8-12V
POWER CONSUMPTION	120mA
OPERATING TEMPERATURE	-5 Deg C - +40Deg C
STORAGE TEMPERATURE	-10Deg C - +50Deg C RH 95% MAX
DIMENSIONS MVC3000-H	24mm(D) X 72mm(L)



WWW.MICROVIDEO.CA

Ph: (800) 213-8111